

WALL MOUNT MINI ODF



FEATURES

- Light and solid structure, dust-proof: Wall mountable
- Ideal for indoor uses - capacity up to 96 cores
- Lock provided on every box ensures the safety of the fibers.
- Optical cables can be lead in/out from upside or downside.
- Adoptable adapter types: SC, LC/Duplex
- Suitable for ribbon or non-ribbon optical fiber cable.

APPLICATION

- Telecommunications subscriber loop
- Fiber to the home (FTTH)
- LAN/ WAN
- CATV

SPECIFICATIONS

Material	Cold rolled steel with electro static spraying
Protection Rate	IP 65
Maximum Adaptor position	96
Cable Inlet & Outlet	8
Dimension	350x380x70 - 24 ports, 400x400x100 - 48 ports 450x400x125 - 72 ports, 550x450x140 - 96 ports
Environmental temperature	-25°C~ + 80°C~
Relative humidity	<85% (When the temperature is below 30°C)
Atmospheric pressure	70~ 106KPa
Insulation resistance	2×10 ⁴ MO/500VDC
Voltage resistance strength	Non-puncture, no arc-over under 3KVDC/1min

PART NUMBER GENERATOR

INTELMDMW24	24 Port Mini Wall Mount Optical Fiber Distribution Frame
INTELMDMW48	48 Port Mini Wall Mount Optical Fiber Distribution Frame
INTELMDMW72	72 Port Mini Wall Mount Optical Fiber Distribution Frame
INTELMDMW96	96 Port Mini Wall Mount Optical Fiber Distribution Frame