

## FREE STANDING CABINETS



### FEATURES

- Simple structure, easy operating, exquisite design and precise dimension;
- Adjustable feet and heavy duty castor available
- Removable side panel & rear door, easy to install and maintain, lock optional;
- Lockable bottom cable entry, adjustable entry size;
- Various optional accessories.
- Static loading: 800kg. (with adjustable feet)
- Available in black and gray
- Height, width, and depth selectable, full range of optional accessories.

### STANDARDS

- Comply with ANSI/EIA RS-310-D, IEC297-2, DIN41494;PART1, DIN41494;PART7, ETSI standard.

### TECHNICAL SPECIFICATIONS

Material	SPCC Cold Rolled Steel
Thickness	Frame 1.2 mm Mounting Rail 2.0 mm Mounting Angle 1.5, Others 1.2 mm
Surface finish	Degreasing, pickling, phosphating, powder coating
Standard Accessories	Top cover-1 No., Frame (nine-fold section steel)-2 Nos., Front door-1 Nos., Side panel-4 Nos., Rear door-1 No., Lock-1 No., Mounting rail-6 Nos., Mounting angle-4 Nos., Bottom plate-6 Nos., Spacer-2 Nos., Fixed shelf-1 No., Heavy duty-4 Nos. castors, Feet-4 Nos., Cage & nuts-40 Nos., Fan-4 Nos., 6-way power strip-1 No., Wrench-1 No.

**TECHNICAL SPECIFICATIONS**

Door Options	Steel Casement door, Smoky –Grey Glass Door, Perforation Steel Door, Double Swing Steel Door, double swing steel door, curved concavo-convex perforation steel door (hexagonal Type), concavo-convex perforation steel door (hexagonal Type)
Static Load Capacity	800Kg

**DIMENSION**

Capacity/U	Width/mm	Depth/mm	Capacity/U	Width/mm	Depth/mm
18U	600	600	42U	600	600
22U	600	600		600	800
	600	800		600	1000
27U	600	600		600	1200
	600	800		800	600
32U	600	600		800	800
	600	800	800	1000	
37U	600	600	47U	600	600
	600	800		600	800
	600	1000		600	1000
	800	800		800	800
	800	1000	800	1000	

**PART NUMBER GENERATOR**

INTELCNF/--/--	Height: 18U, 22U, 27U, 32U, 37U, 42U, 47U
	Width: 600 mm, 800 mm
	Depth: 600 mm, 800 mm, 1000 mm
INTELCNF2266	22U 600 x 600 Free Standing Cabinet
INTELCNF42810	42U 800 x 1000 Free Standing Cabinet